

Product Features

- EGSM-900 60W MCPA Design
- Excellent Suppression IMD
- High linearity and high efficiency
- Suitable for Analog & Digital Modulation
- Feed - Forward Technology Amplifier[FFTA]

Application

- GSM900 Repeater, Booster, BDA, TMA, TMB



1. Electrical Specification.

Parameter	Specification	Remark
Frequency Range	925MHz~960MHz	35MHz BW
Output Power	48dBm(60W)	ALC 49dBm : Min 10dB
Gain	58dB±1dB	
Gain Flatness	±0.5dB	
Gain Variation Over Temp.	±1dB max	-20°C~+60°C
IMD	< -60dBc	CW 10 tone, Ch Sp. : 25KHz
Harmonic	-40dBc max	
Input VSWR	1.5:1 max.	
Output VSWR	1.5:1 max.	Isolator Applied
Normal Operating Voltage	+28V	
DC Current Consumption	17A max.	@48dBm
Shut-down Temp Level	90±5°C	70±5°C Auto Enable

2. Environmental Specification

Parameter	Specification	Remark
Operating Temperature	-20°C~+60°C	
Storage Temperature	-40°C~+85°C	
Relative Humidity	0%~90%	Non-condensing



3. Mechanical Specification.

Physical Dimension : 250mm X 210mm X 40mm

4. Pin Assignment

I/O Interface (D-Sub 9Pin Male)	1. Over Power Alarm	Po=+50dBm±1dB Shutdown High
	2. High Temp. Alarm	High (shut-down) Low (Normal) Alarm & Shutdown +90°C ↑ Auto Recovery +70°C ↓
	3. VSWR Alarm	High (Alarm) Low (Normal) 30dBm(Output Open)
	4. Temp. Monitor	$V_o = (T / 100) + 500mV$
	5. LPA Status	High (Inactive), Low (Active)
	6. Loop Fail Alarm	High (shut-down) Low (Normal)
	7. FWD Power Monitor	4.0V@Po=+48dBm, 0.1V/dB
	8. Enable/Disable	High (Disable) Open & Low (Enable)
	9. GND	
	DC Fail Alarm	≤19V ~ 31V ≤ : Shut down 21V ~ 29V : Auto Recovery
I/O Interface (3W3P Male)	A1. VCC	+28V
	A2. GND	
	A3. N.C	




5. Electrical Test Data


5.1 IMD @Po=+48dBm(CW 10 Tone) / DC 28V, 14.8A


■ Spectrum Analyzer Data

< IMD @ 925MHz >



< IMD @ 942.5MHz >






< IMD @ 960MHz >


Network Analyzer Data

< S11 & Gain >





< Harmonics @ 942.5MHz >



6. Outline Drawing

